



MSD300

NOVASTAR MSD300 SENDING CARD

The MSD300 is a sending card developed by Novastar. It supports 1x DVI input and 2x Ethernet outputs. A single MSD300 supports input resolutions up to 1920x1200@60Hz and loads up to 1,300,000 pixels.

The MSD300 communicates with PC via type-B USB port. Multiple MSD300 units can be cascaded via UART port.

As a highly cost-effective sending card, the MSD300 can be mainly used in the rental and fixed installation applications, such as concerts, live events, security monitoring centers, Olympic Games and various sports centers.



MSD300

NOVASTAR MSD300 SENDING CARD

PRODUCT DETAILS

KEY FEATURES

Supported maximum resolution: 1920x1200@60Hz, downward compatible

1.3 million pixel loading capacity

Pixel level brightness and chroma calibration

1x SL-DVI Input

2x RJ45 Gigabit Ethernet outputs with capacity per port up to 650.000 pixels

1x Light Sensor connector for automatic LED brightness adjustment

2x UART control ports for up to 20 cascading devices

1x Type-B USB port

SPECIFICATIONS

Input Voltage	DC 3.3V to 5.5V
Rated Power Consumption	3W
Rated Current	0.6A
Working Temperature	from -20°C to +75°C
Working Humidity	from 10% RH to 90% RH, non-condensing
Product Size	138.8 x 120.6 x 22 mm (5.46 x 4.75 x 0.87 in)
Product Weight	104.3 g (0.23 lbs.)
Packing Size	355 x 190 x 62 mm (13.98 x 7.48 x 2.44 in)