

## HMX-44 PLAY


# RACKMOUNT 4-IN / 4-OUT MATRIX MIXER WITH MULTI-PLAYER

HELVIA has thought to respond to the main needs of those involved in small-to-medium audio installations offering versatility and compactness in an integrated solution such as the HMX-44.

This is a little gem that integrates a matrix with a 4-input, 4-output mixer and a multimedia player. The mixer section provides 3 combo Mic-Line inputs with 48V Phantom, a front mini-jack stereo Line input combined with the multimedia player with DAB+, FM, USB, BT. Each input has independent level adjustment, and the 3 combo Mic/Line inputs also feature high and low tone adjustment.

All 4 inputs are assigned independently to the 4 zones, and each zone has output level control.

The HMX-44 provides connection with HMX-MIC microphone base station via RJ-45 connection. The station is equipped with alert chimes and allows the 4 zones to be selected independently.



HMX-44 PLAY

# RACKMOUNT 4-IN / 4-OUT MATRIX MIXER WITH MULTI-PLAYER

## PRODUCT DETAILS

### KEY FEATURES

4-In / 4-Out Matrix

4-channel mixer with 3 combo Mic/Line inputs and 1 Mini-jack Stereo Front input

RCA Line Outputs

Multimedia Player with DAB+, FM, USB, BT and Remote Control

48V Phantom Power for condenser microphones and Priority on Mic 1

Small size in 1 rack unit

Mute function in case of emergency

### SPECIFICATIONS

<b>Frequency response</b>	100Hz - 24kHz
<b>THD</b>	<0.76% @ 1kHz
<b>Input impedance</b>	1k Ohms (mic/line)
<b>Input sensitivity</b>	-11dB (line), -46dB (mic)
<b>SNR</b>	84dB (line), 82dB (mic)
<b>Inputs</b>	1Mic (XLR), 2 x mic/line (XLR/jack), 1 Line (RCA/Euro-block terminal)
<b>Zone Line Outputs</b>	4 x RCA (mono) outs
<b>Multimedia Player</b>	DAB+/FM/USB/BT
<b>Phantom power</b>	+48V switchable on each XLR Input
<b>Mute</b>	+24V Relay Contacts

## HMX-44 PLAY

# RACKMOUNT 4-IN / 4-OUT MATRIX MIXER WITH MULTI-PLAYER

---

<b>Bluetooth Version</b>	2.0
<b>Call Station Port</b>	RJ45 Port (with power)
<b>Power supply</b>	170-264Vac, 50Hz (IEC)
<b>Fuse</b>	T1A/250V
<b>Unit Dimensions</b>	435 x 122 x 44mm (17.1 x 4.8 x 1.7 in)
<b>Packing Dimensions</b>	550 x 227 x 69 mm (21.6 x 8.9 x 2.7 in)
<b>Weight</b>	1.8 kg – 4 lbs.
<b>Packing Weight</b>	2,74 kg – 6 lbs.