

The REDY+630SET is the answer to all those small audio amplification needs (small shops, multimedia educational contexts, etc.) where practicality, ease of installation, multi-functionality and compactness need to coexist in perfect harmony.

The system consists of a pair of 2-way ported speakers with 6.5" woofer and 0.5" tweeter. One of the speakers is active and features a 30+30W RMS (100+100W Peak Power) Class-D amplifier and a media player with USB input, Line Stereo input and BT streaming. The other speaker is passive and is connected to the first speaker to create a perfect stereophonic sound system.

The Line Stereo input is equipped with RCA, 1/8" mini jack and Phoenix connectors, allowing connection to a wide range of portable (CD, DVD, Tuner, etc.), multimedia (mobile phones, tablets, etc.) and fixed sources. The system is also equipped with a stereo Link Out and a mono subwoofer output. This allows the REDY-630SET to be expanded to include additional speakers or sound systems.

BT streaming and remote control also allow wireless operation. Use your own BT devices and access your own playlists. It also available the TWS (True Wireless Stereo) function and let the user connect to a second REDY-630SET and use the additional active speaker as Right channel or simply as wireless audio link.











FRENEXPORT





### FRENEXPORT



## **PRODUCT DETAILS**

### **KEY FEATURES**

2x30W RMS (2x100W Peak Power) Class-D Power Amplifier			
2-Way Ported Speakers with 6.5" Woofer and 0.5" Tweeter			
C-shaped Brackets with Adjustable Horizontal Angle			
BT/USB/Line-In Player with Remote Control			
Stereo Line input with RCA, Mini-jack and Phoenix connections			
2-Band EQ, Link Out and Sub Out			
True Wireless Stereo (TWS) function			

## **SPECIFICATIONS**

Speaker Type	2-Way Active Speaker		
Frequency Response	70 Hz - 20 kHz @ -10 dB		
Max SPL	104 dB		
Sensitivity	90 dB (1W @ 1m)		
Amplifier	Class-D		
RMS Power	30 W		
Peak Power	100 W		
LF Туре	6.5" Paper Cone Woofer with Rubber Edge		
Impedance	8 Ohm		
НҒ Туре	0.5 Mylar Dome Tweeter		

#### FRENEXPORT



Crossover Frequency	7.0 kHz		
Directivity (HxV)	100° x 100°		
Input Connections	1/8" Stereo Jack, Stereo RCA, 5-pin Phoenix, Binding Post to Passive Speaker (Red/Black)		
Output Connections	1/8" Stereo Jack (Link Out), 1/8" Mono Jack (Sub Out), 2-pin Phoenix (Right Speaker Out)		
Controls	Line/Aux/RCA In Volume, Power On Led (Blue)		
EQ Controls	Low 20Hz +/- 12 dB; High 20kHz +/- 12 dB		
Multimedia Player Controls		Cycle, Mode, Song +/-, Rew, FF, Play/Pause, TWS	
Power Requirement		100-240 Vac - 50-60 Hz	
Power Consumption		100W	
Fuse		T2A - 250V (internal)	
Housing material		PP	
Grille material and thickness		0.6 mm, Steel	
Wall-Mount		C-Bracket with horizontal adjustment	
Speaker Dimension (WxDxH)		215 x 197 x 298 mm (13.2 x 14.8 x 11.7 in)	
Net Weight		3,8 kg (8.4 lbs.)	
Packing Dimension - Pair (WxDxH)		483 x 288 x 345 mm (19.0 x 11.3 x 13.6 in)	
Gross Weight		7,7 kg (17.0 lbs.)	

FRENEXPORT