

NP2X

1/4" PROFESSIONAL PHONE PLUG, 2 POLE, NICKEL CONTACTS, NICKEL SHELL

The heavy duty professional phone plug series improves on the design of the existing C series by offering the thinnest available A-gauge 1/4" plug with unique Neutrik chuck type strain relief on the market. The slimline shell with a width of 14.5 mm meets the most recent requirements for highest density jackfields (15.88mm jack pitch). The precise machined one-piece tip contact without rivets makes it unique and avoids hook up in a socket or break off the tip. The Plug X Series serves all applications such as guitar applications, audio cables, snakes, speakers, amplifiers and mixing desks.



NP2X

1/4" PROFESSIONAL PHONE PLUG, 2 POLE, NICKEL CONTACTS, NICKEL SHELL

PRODUCT DETAILS

KEY FEATURES

Extra slim 1/4" plug for highest packing density

Robust diecast shell in stylish design

Proven chuck type strain relief for reliable cable retention

Sleek design for best handling convenience

Precision machined one-piece contacts - avoid hook up of tip contact

SPECIFICATIONS

Connection Type	plug
Gender	male
Contact resistance	depends on mating connector mW (inner)
Dielectric strength	1 kVdc
Insulation resistance	> 2 GOhm
Rated current per contact	depends on mating connector
Rated voltage	50 V
Cable Diameter	4 - 7 mm
Lifetime	> 1000 mating cycles
Wiring	Solder contacts
Contact plating	2 µm Ni (Su)
Contacts	Brass

NP2X

1/4" PROFESSIONAL PHONE PLUG, 2 POLE, NICKEL CONTACTS, NICKEL SHELL

Insert	Polyamide (PA 6.6 30 % GR)
Shell	Zinc diecast
Shell plating	Nickel
Strain relief	Polyacetal (POM)
Temperature range	-20 °C to +65 °C