

50'S MODIFIED ESQUIRE NECK, 22 NARROW TALL FRETS, 9.5", U SHAPE, ROASTED MAPLE

There's no denying the allure of a roasted maple neck. Resistant to humidity shifts and featuring a gorgeous, dark look, they have more sustain and add a unique note to the instrument's voice. This roasted maple Modified Esquire neck has the back shape of an early 50's Esquire but with a flatter fingerboard radius and larger frets for modern playability.

Fender replacement necks are made at Fender manufacturing facilities to the same specifications as those used on our instruments. This Ensenada, Mexico-made Esquire neck features a maple fingerboard, a 9.5" radius and 22 narrow tall frets. The one-piece roasted maple neck has a thick early 50's "U" profile with a smooth satin urethane finish on the front and back of the neck. The headstock has a gloss finish with an authentic "Esquire" decal to complete the classic look.

The bone nut is pre-slotted with "pilot" string location grooves to make spacing a breeze when performing the final string slot filing. For true Fender authenticity, it's also serialized and stamped, with genuine headstock logo decal.

This replacement neck is for a Fender or Squier® by Fender guitar.

Because Fender genuine replacement necks have not been mounted to guitar bodies, nut slots must be cut by qualified personnel. Other installation processes may be required, such as fret work, fitting the neck to the neck pocket, and other instrument setup procedures. Your local FMIC Authorized Service Center can install genuine replacement necks; find <u>Authorized Service Center</u> locations near you in the "Support" section of fender.com.





50'S MODIFIED ESQUIRE NECK, 22 NARROW TALL FRETS, 9.5", U SHAPE, ROASTED MAPLE







50'S MODIFIED ESQUIRE NECK, 22 NARROW TALL FRETS, 9.5", U SHAPE, ROASTED MAPLE

PRODUCT DETAILS

KEY FEATURES

Replacement neck is for a Fender or Squier® by Fender guitar

Early 50's "U"-shaped

The headstock has a gloss finish with an authentic "Esquire" decal

The bone nut is pre-slotted with "pilot" string location grooves

Serialized and stamped, with genuine headstock logo decal

SPECIFICATIONS

Neck finish	Satin Urethane with Gloss Urethane Headstock Face	
Neck thickness	1st Fret880" (22.35 mm), 12th Fret990" (25.15 mm)	
Neck mounting	4-Bolt	
Fingerboard radius 9,5" (241 mm)		
Fingerboard material	Roasted Maple	
Position inlays	Black Dot	
Side dots	Black Micarta, 3/32" (2.38 mm)	
Number of frets	22	
Truss rod	Standard	
Truss rod nuts	3/16" Hex Adjustment	
String nut	Bone	
Nut width	1.650" (42 mm)	





50'S MODIFIED ESQUIRE NECK, 22 NARROW TALL FRETS, 9.5", U SHAPE, ROASTED MAPLE

Nut material	Bone	
Tuner mounting config	Dual Guide Pin	
Headstock thickness	.540" (13.71 mm)	
Peg hole diameter	.397" (10.08 mm)	
Scale lenght	25.5" (64.77 cm)	

