

VERITAS10 10" FULLRANGE POWERED HIGH PERFORMANCE SPEAKER 1000 WATT

The NOVA VERITAS series brings it to the point: Maximum performance meets uncompromising features. VERITAS is made for pro rental applications and installers. VERITAS are high grade speakers, offering dynamic, most neutral andauthentic sound quality. The acoustic features of all VERITAS models fulfill highest demands on sound quality, excellent speech intelligibility and offera thrilling live performance. The integrated high-performance amplifier modules of all models make the VERITAS speakers to modern, professional audio tools.











VERITAS10

10" FULLRANGE POWERED HIGH PERFORMANCE SPEAKER 1000 WATT

PRODUCT DETAILS

KEY FEATURES

Outstanding dynamic sound and excellent headroom

High sound pressure and precise tonal accuracy

Attractive, elegant and stylish discreet

Perfect dispersion of 90° x 40° (HxV)

Wide range of accessories

Program Power: 1000 watt (500 watt RMS)

SPECIFICATIONS

System Type	Self-powered 10" two-way, multifunctional vented cabinet
Frequency Range (-10 dB)	50 Hz 22 kHz
Frequency Response (±3 dB)	55 Hz 20 kHz
Coverage Pattern	90°x 40° nominal
HF Horn	Fibreglass horn (rotatable)
Crossover Modes	Passive
Crossover Frequency	1600 Hz
Power Rating (Continuous** / Program)	500 W RMS amplifier (@ 8 ohms), 500 W / 1.000 W (speaker power capability)
Maximum SPL*** 128 db	SPL peak
System Sensitivity (1w/1m) 98 db S	PL
LF Driver 1 x 10"	NOVA 10/500 (2.5 in. voice coil)





VERITAS10

10" FULLRANGE POWERED HIGH PERFORMANCE SPEAKER 1000 WATT

LF Nominal Impedance	8 ohm	
HF Driver	1 x NOVA T5000, 1.75 in. voice coil comp. driver	
Active Tunings	Low cut, high boost, low boost	
Enclosure	15mm, birch plywood	
Suspension/Mounting	35 mm pole socket, 2 x M10 fixing points, 5 x ANCRA(comp.) track, monitor angle 45°	
Transport	2 integrated handles	
Finish	Black NOVA PolyCoat© finish	
Grille	Powder coated, black, perforated steel with acoustic transparent charcoal foam backing	
Connectors	Input	
Output	2 x XLR LINK male, 1 x XLR mix output	
Dimensions	(WxHxD) 314 mm x 560 mm x 298 mm	
Peso Netto	19,50 Kg	
Optional accessories	FP2 Flexible tilt / pitch (Article number	

