


WF-U216PP

UHF DUAL 16-CHANNEL WIRELESS SYSTEM WITH TWO HEADSET MICS AND TWO BODYPACKS

The WF-U216 is a UHF dual wireless microphone system with 16 channels each. Its main characteristics are reliability, audio quality and extreme simplicity of use. It's been designed for all those professionals who need a ready-to-use tool, always. Despite its minimalist look, the WF-U216 is a concentrate of technology, capable of integrating a high-quality microphone preamp stage, a DSP-based audio processing, a PLL synthesis stage, and other functions in a single chip. Compared to analog systems, it significantly improves the stability and reliability of the FM modulation section, the AF and audio stages, offering professional level music performance. The WF-U216 is also equipped with the IR synchronization system, for quick coupling between the receiver and transmitter. Both the hand transmitter and the pocket transmitter can work with AA alkaline or rechargeable batteries. The quality of the headset cardioid capsule (condenser) is professional.



WF-U216PP

UHF DUAL 16-CHANNEL WIRELESS SYSTEM WITH TWO HEADSET MICS AND TWO BODYPACKS

PRODUCT DETAILS

KEY FEATURES

520-550MHz UHF Band

16-Channels for each Microphone (32-channels in total)

Simple and Outright User Interface with display on Transmitters and Receiver

Single-chip design with high-quality preamp, DSP audio processing, and PLL synthesis

IR Matching System for Quick Setup

High efficiency battery consumption design.

50m Ideal Distance (without obstacles)

Body-pack with 3-Pin Mini-XLR Connector and LCD display (WF-U216HP and PP models only)

Professional and Lightweight Headset with High-Sensibility Condenser Cardioid Capsule (WF-U216HP and PP models only)

SPECIFICATIONS

Carrier Frequency	UHF 520-550MHz
Frequency Stabilization	Automatic calibration
Dynamic Range	>90dB
Total Harmonic Distortion	<0.4%
Frequency Response	40Hz-15KHz \pm 3dB
System Audio Output Level	Balanced 400mV; Unbalanced 400mV
System Packing Dimensions (WxDxH)	380 x 285 x 65 mm
System Packing Gross Weight	1.2 kg

WF-U216PP

UHF DUAL 16-CHANNEL WIRELESS SYSTEM WITH TWO HEADSET MICS AND TWO BODYPACKS

Receiver Power Adapter	DC 12V / 1000mA
Receiver Consume Power	<4W
Receiver Signal/Noise Ratio	>95dB
Receiving Sensitivity	-95dBuV
Receiver De-Emphasis	75uS
Receiver Size (WxDxH)	210 x 155 x 43 mm
Receiver Antennas Height	115 mm
Receiver Net Weight	0.345 kg
Transmitter Power	10mW (Max)
Transmitting Modulation Type	FM
Transmission Max Deviation	±26KHz
Transmission Spurious Emission	>40dB
Transmitter Battery Voltage	2x1.5V AA Alkaline Batteries or 2x1.2V Rechargeable
Transmitter Continuous Using	about 5 hours
Pocket Transmitter Size (WxDxH)	62 x 30 x 103 mm
Pocket Transmitter Antenna (W/DxH)	Ø3 x 10 mm
Pocket Transmitter Net Weight	0.133 kg (batteries included)