

GA43L

4X750W CLASS D 4 CHANNEL AMPLIFIER

GA43L is a compact 4-channel high-efficiency Class D amplifier featuring a Powersoft™ power module, capable of delivering up to 4x750W per channel at 4 ohms or 2x1500W at 8 ohms / 100V.

This powerful amplifier is designed for high-performance applications in both rental and permanent installations.



GA43L

4X750W CLASS D 4 CHANNEL AMPLIFIER

PRODUCT DETAILS

KEY FEATURES

Four Channel Class D Amplifier

Compact and modular design

Fits very well fixex installations

Use optional G-RACK to fit in a 2U Rack up to 3 amps

Volume control Knob

Thermal protections (power limiting - thermal shutdown)

Short-circuit overload output protections

Stationary high frequency protection

SPECIFICATIONS

Input Channels	4
Output Channels	4
Max Output Power per Channel	750 Watt @ 4 ohm
Minimum Impedance	4? (2? musica di sottofondo)
High Impedance Speaker Lines	70V-100V
Operating Voltage	100-240V
AC Current	10A Nominal
Dimensions WxHxD	145mm x 90mm x 418mm
INPUT	Analog Balanced 4x XLR M
Power OUTPUT	2 x Speakon out (4 pole)