

SQUARE 150P 150W LED PROFILE SPOT LIGHT WITH BEAM SHAPING SHUTTERS & GOBO SLOT

Centolight SQUARE 150P is a professional LED Profile with 26° beam (also available optional 19° lens tube) designed for theatres and fixed installations where high LED chip reliability and warm white lighting (approx. 3.200K) are required.

The light source is a 150W CITEDLED® LED with CRI >90 to allow excellent color rendering, especially in indoor venues like TV studios, theaters and museums. Great attention is paid to quality of dimmer control and chip temperature, to minimize the consequences of using LEDs instead of traditional lamps.

The cooling system uses high precision fans in order to keep noise within 25dB @ 1m. The 4 beam-shaping shutter system allows both radial and angled adjustment of the beam. The fixture is equipped with a compartment for gobos and manual iris (both optional), as well as the front color-frame holder (included).



SQUARE 150P

150W LED PROFILE SPOT LIGHT WITH BEAM SHAPING SHUTTERS & GOBO SLOT

HIGHLIGHTS



ENERGY-SAVING LIGHT SOURCE WITHOUT COMPROMISE

Never more than today the world of entertainment and theatrical lighting is sensitive to environmental themes, not only because we care about our planet's health and must demonstrate in every day's choices, but also because it involves money-saving aspects.

The Square 150P by Centolight features selected 150W Cited Led chips, which guarantee a high CRI value (Color Rendering Index greater than 90), 50,000 hours chip lifecycle, 65%-70% energy saving compared to normal halogen lamps.

GREAT ATTENTION IN MANUFACTURING QUALITY AND WIDE RANGE OF ACCESSORIES

Square series by Centolight is the result of a wise selection in the materials and, most of all, in construction, trying to focus on the real essential aspects to guarantee professional performance without losing sight of the budget.

The Square 150P features 26° tube lens and color frame holder. However, a 19° lens tube (Square Lens-19) is also available. In addition, it is possible to mount a manual Iris to limit the aperture from 79mm up to 4mm, and a gobo holder to use 57mm metal or glass gobos (optional).



SQUARE 150P

150W LED PROFILE SPOT LIGHT WITH BEAM SHAPING SHUTTERS & GOBO SLOT

PRODUCT DETAILS

KEY FEATURES

LED Profile Spot with 26° Beam (19° optional)

Light Source: 150W Warm-White (3200K) CITEDLED® LED with over 50,000h lifetime

Radial/Angled Blade-Framing System

Smooth 16-bit Dimmer

Flicker-Free Operation

Low-Noise Cooling System

Gobos/Iris Slot (optional gobo and iris)

Color Frame Holder (included)

SPECIFICATIONS

Light Source 1 x 150W Warm White Citedled® LED

Chip Life Over 50,000h

CCT (Color Temperature) 3100±150K

Luminous Flux 3120lux/3m, 1170lux/5m, 780lux/10m

CRI >90

Refresh Rate Over 15.000Hz (Flicker-Free)

4 Blade-Framing System adjustable for radial and angle positioning

Beam Angle 26° Lens (19° Optional)

16-Bit Smooth Linear Dimming

SQUARE 150P

150W LED PROFILE SPOT LIGHT WITH BEAM SHAPING SHUTTERS & GOBO SLOT

Strobe	0-20Hz
Cooling System	Quiet Fan (under 25dB @1m)
DMX Channel	2-Channels (RDM Included)
Control Modes	DMX, Master-Slave, Manual Dimming
LCD Display	
DMX In/Out	3-pin XLR
IP rate	IP33
Power Socket	Powercon Input/Output
Voltage:100~240V 50/60Hz	
Max Power Consumption	170W
Working Temperature	-30÷55°C
Housing Surface Temperature	40°C~55°C
Max. Fixture Size (WxDxH)	590 x 266 x 266 mm – 23.29 x 10.47 x 10.47 in (C-bracket included)
Net Weight	6,5 kg – 14.33 lbs.
Packing Size (WxDxH)	640 x 280 x 280 mm – 25.20 x 11.02 x 11.02 in
Packing Weight	8,2 kg – 18.08 lbs.
Accessories	19° Lens Tube, Metal Gobo Holder, Iris