

GP18A

KGear GP18A POWERED 18" SUB + 24X2" COLUMN SYSTEM

GP18A

Subwoofer 18" + sistema modulare array a colonna 24x2" (Amplificato)

GP18A è un sistema sub e colonna costituito da un subwoofer Heavy duty da 18" amplificato in combinazione con 3 moduli ognuno equipaggiato con 8 trasduttori in array da 2", tecnologia PAT® K-array™ technology. E' in grado di amplificare fino a 3 sistemi passivi GP18 in configurazione stereo. Il sistema incorpora DSP e amplificatore Powersoft™ con controllo remoto via ethernet e software di controllo Armonia™.

Progettato per elevate prestazioni sia in applicazioni indoor che outdoor molto versatile sia per rental che installazione fissa in ambito touring, musica da vivo, auditorium e club.

High performance to size/weight ratio featuring easy and fast setup possibility.

Il punto di forza nella concezione del sistema si trova considerando le eccellenti prestazioni in relazione al rapporto dimensioni e peso, con obiettivo semplicità e rapidità di setup.

Suggerimento utenti: ottimizzate il cost combinando GP18A con il modello passivo GP18 per configurazione stereo o per estendere il cluster. Progettato per elevate prestazioni sia in applicazioni indoor che outdoor molto versatile sia per rental che installazione fissa in ambito touring, musica da vivo, auditorium e club.



GP18A

KGear GP18A POWERED 18" SUB + 24X2" COLUMN SYSTEM

PRODUCT DETAILS

KEY FEATURES

Powered PA 18" Subwoofer + Column system expandable with 18" GP18 passive subwoofer

4 channel amplifier able to power a second GP18 sub + column system for stereo configuration

Powersoft™ DSP and amp module with Armonia™ control software

Trustability, high performances, elegant design

Common Applications: Live music, Karaoke, DJ set, Wedding parties, entertainment event in general

SPECIFICATIONS

GENERAL SPECIFICATIONS

Type Powered Sub + Column line array system

Transducers SUB - 18" woofer, TOP - 3 modules with 8x2" ferrite magnet woofers

Frequency Response 30Hz-20kHz (-6 db)

Max. SPL?125dB (calculated using a signal with crest factor 4 (12dB) measured at 1 mt)

Coverage V. 20° | H. 140°

Amp Module 4 channel Class D

Output power 4 x 1500 W @ 4 ohm

Power 500W Rated Load (1/8 Max Output Power)

Consumption

DSP features Remote control and tuning, Input and Output Delay, Parametric input EQ, Output parametric filters

GP18A

KGEAR GP18A POWERED 18" SUB + 24X2" COLUMN SYSTEM

Connectors	Volume potentiometer, RJ45 for remote control, 2x Combo XLR Input, 2x SpeakON Output, 1x PowerCon True AC MAINS
Controls	Volume potentiometer, Preset selector, Remote control through Powersoft ArmoniaPlus Software
HANDLING & FINISHES	
Dimensions (WxHxD)	545 x 2220 x 600 mm (21,46 x 87,40 x 23,6 in)
Weight	43 kg (94,8 lb)
Material	Subwoofer Birch in Plywood, Column in ABS
Finishing	Black