

## HCMA-PLAY MIC 2 ZONES REMOTE PAGING MICROPHONE BASE

HCMA-PLAY MIC integrates a microphone base with gooseneck microphone, **bi-zone control** with in-out message ringtone. Connection, through a common CAT5 or CAT6e cable, integrates power supply, control, and audio output, to simplify installation as much as possible.

It is also possible to connect more HCMA-PLAY MIC bases, thanks to the RJ-45 link output. Finally, the **one-touch-to-talk** function greatly facilitates the daily use of the microphone base.



# HCMA-PLAY MIC

## 2 ZONES REMOTE PAGING MICROPHONE BASE

### PRODUCT DETAILS

#### KEY FEATURES

Sturdy and lightweight construction for maximum durability

RJ-45 interface for power supply & signal transmission

Built-in chime for paging reminder

RJ-45 Link Port for cascade connection of multiple microphone bases

One-touch-to-talk operation for convenient use

#### SPECIFICATIONS

<b>Sensitivity</b>	+/- 10mV
<b>Frequency Response</b>	200Hz – 15kHz
<b>SNR</b>	= 60dB
<b>RJ-45</b>	RS-485 Communication Protocol
<b>Power Supply</b>	Host (Provided by Amplifier unit)
<b>Size (WxDxH)</b>	40x150x100 mm
<b>Net Weight</b>	0,55 kg