

10" PASSIVE 2-WAY LOUDSPEAKER

A versatile PA/monitor speaker series that is compact in size and perfect for near-field monitoring – yet can deliver highquality sound to the corners of the room. Boasts multiple installment options for easy set up.











10" PASSIVE 2-WAY LOUDSPEAKER

PRODUCT DETAILS

KEY FEATURES

Two-way full range speaker with 10-inch LF driver and a 1-inch compression driver.

Passive crossover board features separate cooling zones to ensure safe and continuous operations in the toughest environments.

Wide dispersion of 90×60 degrees, with rotatable horn for horizontal installation.

Designed for fixed and mobile applications, with a wide array of flying options.

Features top hats for quick set-up.

NL4 INPUT and LINK OUT connections as standard.

Robust enclosure made from premium multi-laminate birch plywood.

Impact resistant textured paint finish.

SPECIFICATIONS

Enclosure Type	Two-way passive, reflex-loaded
Frequency Response	70 Hz to 20 kHz
Sensitivity (1 W/1 m)	94 dB
Nominal Impedance	8 ohm
Power Handling	400 W RMS, 800 W Program
Maximum SPL	120 dB cont., 126 dB peak
Dispersion	90 °H × 60 °V, Rotatable
Driver Configuration 10 inch (250 mm) neodymium LF cone driver,1 inch (25 mm) exit neodymium HF compression driver	
Crossover	Asymmetric internal passive crossover
Connectors	2 × Neutrik SpeakON™ NL4
Dimensions	(W×H×D) 292 × 508 × 280 mm (11.5 × 20 × 11 inch)





XY-101

10" PASSIVE 2-WAY LOUDSPEAKER

Weight 14 kg (30.9 lbs)

Rigging and Hardware 8 \times M8 threaded mounting points (4 top/4 bottom),3 \times M8 threaded mounting points on rear,4 \times M8 threaded mounting points on side (2 left/2 right),4 \times M6 threaded points on rear (for wall mount bracket),1 \times flush handle on rear,1 \times 35 mm polemount socket

Grille Hex punched steel

Enclosure 15 mm (0.6 inch) birch plywood

Finish Impact-resistant, Black semi-matt textured

Suggested Power Amplifier/Recommended K2DSP /M30DHDSP

Accessories polemount socket cover(-W model only)

