


## VENU 12

# PASSIVE 12" TWO-WAY SURFACE MOUNT LOUDSPEAKER

---

The 12" based Venu 12 has been designed to offer everything you could ask for from an installation loudspeaker. The entire Venu series has been created from the demands of many leading installation contractors and engineers around the world. There are many features that make the passive two-way Venu 12 so convenient to install and use: the Easy Hang wall bracket that supports the enclosure, either vertically or horizontally, and requires only one set of hands to attach the enclosure; the Phoenix connector with link through for quick and reliable hook ups; the rotatable 90° horizontal by 60° vertical high frequency horn allowing the correct dispersion to be maintained in vertical or horizontal mounting positions; electronic high frequency protection for increased reliability; M8 flying points for horizontal ceiling suspension; weather-resistant grille and fittings suitable for beach bars and other corrosive environments; the rotatable logo to allow for correct display in either vertical or horizontal positions; and an enclosure made entirely from 15 mm multi-laminate birch plywood.



VENU 12

# PASSIVE 12" TWO-WAY SURFACE MOUNT LOUDSPEAKER

## PRODUCT DETAILS

### KEY FEATURES

Compact and unobtrusive appearance

Rotatable 90°H x 60°V HF waveguide

12" low frequency driver

1" high frequency compression driver

Textured polyurethane finish, optional custom colours

Multiple internal M8 rigging points

Weather-resistant, perforated steel grille

Applications: bar, club, lounge, hotel, restaurant

### SPECIFICATIONS

<b>Frequency Response</b>	50 Hz - 22 kHz $\pm$ 3 dB
<b>Efficiency</b>	98 dB 1w/1m
<b>Crossover Point</b>	1.9 kHz passive
<b>Impedance</b>	8 ohms
<b>Power Handling</b>	400 Watts AES
<b>Maximum Output</b>	124 dB cont, 127 dB peak
<b>Driver Configuration</b>	1x12" LF, 1x1" HF compression driver
<b>Dispersion</b>	90°H x 60°V rotatable
<b>Protection</b>	HF electronic device

# VENU 12

## PASSIVE 12" TWO-WAY SURFACE MOUNT LOUDSPEAKER

---

<b>Connectors</b>	1 x Phoenix with link out
<b>Enclosure</b>	15 mm birch plywood
<b>Finish</b>	Textured polyurethane
<b>Grille</b>	Weather-resistant perforated steel with foam filter
<b>Dimensions (WxHxD)</b>	385x522x330 mm
<b>Weight</b>	19.5 kg