





## CM-S56T-K 6" SURFACE MOUNT LOUDSPEAKER (COUPLE)

Drawing on our club loudspeaker manufacturing heritage, the versatile two-way CM-S54T, CM-S56T and CM-S58T produce premium-quality audio. Available in black or white, these new units are perfect for discreet installation in a variety of spaces where reliability is crucial, and the loudspeakers can even be used for some applications outdoors.

These affordable and adaptable new arrivals in the CM Series include a host of features including transformer taps – ideal if you need a professional and adaptable fixed installation solution.



# CM-S56T-K 6" SURFACE MOUNT LOUDSPEAKER (COUPLE)

## PRODUCT DETAILS

### KEY FEATURES

Soft dome tweeter

Newly developed Vortex Bass Accelerator

Flexible 8 ohms impedance

Dust and water resistant

U bracket

Original curved enclosure design

Color: Black

### SPECIFICATIONS

Two-way passive, reflex-loaded

Frequency response (- 10 dB, Typical) 80 Hz - 20 kHz

Sensitivity (1W/1m) 88 dB

Nominal Impedance 8 ?

Power Handling (RMS/Program) 60 W / 120 W \* IEC60268-5

**Transformer taps 70 V** 60 W / 30 W / 15 W / 7.5 W

**Transformer taps 100 V** 60 W / 30 W / 15 W

Dispersion 110 °H x 110 °V

Maximum SPL 113 dB (peak) \* Calculated from the power handling and sensitivity

**LF** 6" (152 mm) cone

**HF** 1" (25 mm) silk dome tweeter

**Connectors Euroblock (4 pin) x 1 (input** +/-, loop-thru

# CM-S56T-K

## 6" SURFACE MOUNT LOUDSPEAKER (COUPLE)

<b>Rigging and Hardware</b>	1 x U-bracket 2 x M6 threaded mounting points on rear
-----------------------------	---

<b>Grille</b>	Punched Aluminum
---------------	------------------

Enclosure PP

Dimensions ( WxHxD) 214.1 x 332.3 x 183.5 mm

<b>Weight</b>	5.1 kgs
---------------	---------

Environmental IP54