

CIRRUS6

# PASSIVE 6" TWO-WAY FULL RANGE CEILING LOUDSPEAKER

The Cirrus 6 two-way full range passive ceiling loudspeaker brings Void quality and attention to detail to the commercial install sector. It consists of a 8" low frequency driver and a coaxially mounted 0.5" high frequency tweeter, housed in a white powder coated ceiling mount frame. The Cirrus 6 can be installed and deployed in record breaking time thanks to the half-turn spring-loaded retention clips and the input selector switch that attenuates a 70/100V line distributed feed to the required output level with voltage taps at 3.75 watts, 7.5 watts, 15 watts, and 30 watts, as well as a low impedance (8 ohm) 75 watt setting. The use of separate low frequency and high frequency drive units results in a discreet and space-saving package with very flat and wide response up to 20kHz, providing uniform 80° dispersion over a wide area.



CIRRUS6

# PASSIVE 6" TWO-WAY FULL RANGE CEILING LOUDSPEAKER

## PRODUCT DETAILS

### KEY FEATURES

Internal 100V/70V line transformer

Selectable voltage taps and low impedance setting

Wide conical 80° dispersion pattern

Paintable white ABS enclosure

6.5" low frequency driver

1" coaxially mounted high frequency driver

Quick and easy ceiling mount fixings

Applications: hotels, restaurants

### SPECIFICATIONS

<b>Frequency Response</b>	60Hz - 20kHz $\pm$ 3dB
<b>Efficiency</b>	88dB 1w/1m
<b>Impedance</b>	Selectable 8 ohms or 70/100V line
<b>Power Handling</b>	Selectable 3.75W/7.5W/15W/30W (8 ohms 75W)
<b>Maximum Output</b>	106dB
<b>Driver Configuration</b>	1x6.5" LF, 1x1" coaxial HF tweeter
<b>Dispersion</b>	80° from central axis
<b>Dimensions (WxD)</b>	267x162 mm
<b>Weight</b>	2.7kg

# CIRRUS6

## PASSIVE 6" TWO-WAY FULL RANGE CEILING LOUDSPEAKER

---

<b>Enclosure</b>	ABS (White RAL 9016)
<b>Grille</b>	Powder coated (white RAL 9016) steel mesh
<b>Construction Note</b>	Mounting hole 240mm (9.45") diameter