


XY-115S-W

HIGH-POWER SUBWOOFER WITH AN 15-INCH, LOW-FREQUENCY DRIVER.

A versatile PA/monitor speaker series that is compact in size and perfect for near-field monitoring – yet can deliver high-quality sound to the corners of the room. Boasts multiple installment options for easy set up.



XY-115S-W

HIGH-POWER SUBWOOFER WITH AN 15-INCH, LOW-FREQUENCY DRIVER.

PRODUCT DETAILS

KEY FEATURES

High-power subwoofer with an 15-inch, low-frequency driver.

Capable of reproducing deep bass as low as 45 Hz without distortion.

Strong pillars installed in the cabinet ensure rigidity against the most powerful bass.

Requires an active crossover to set the necessary frequency range

NL4 INPUT and LINK OUT connections as standard.

Pole mount for quick set-up with other Pioneer products.

Robust enclosure made from premium multi-laminate birch plywood.

Color: White

SPECIFICATIONS

Enclosure Type	Single driver, reflex-loaded subwoofer
Frequency Response	45 Hz to 150 Hz
Sensitivity (1 W/1 m)	96 dB (half space)
Nominal Impedance	8 Ohm
Power Handling	700 W RMS, 1400 W Program
Maximum SPL	124 dB cont., 130 dB peak (half space)
Driver Configuration	15 inch (380 mm) neodymium LF cone driver
Connectors	2 x Neutrik SpeakON™ NL4
Dimensions (WxHxD)	472 x 466 x 510 mm (18.6 x 18.3 x 20.1 inch)

XY-115S-W

HIGH-POWER SUBWOOFER WITH AN 15-INCH, LOW-FREQUENCY DRIVER.

Weight	30 kg (66.1 lbs)
Rigging and Hardware	2 x flush handles (1 left/1 right), 1 x M20 polemount socket for mid/high enclosures, 4 x rubber feet (bottom) and 4 x mating recesses (top)
Grille	Hex punched steel
Enclosure	15 mm (0.6 inch) birch plywood
Finish	Impact-resistant, Black semi-matt textured
Suggested Power Amplifier	K3DSP
Accessories	polemount socket cover(-W model only)