

KIRA5 5"/2-WAY COAXIAL PREMIUM LOUDSPEAKER/150 W (RMS)

The KIRA5 is a coaxial two-way high performance loudspeaker for fixed installations and mobile use. The cabinet is equipped with a 1" HF driver (1,35" voice coil), which is mounted coaxially onto the 5" transducer. KIRA5 offers a coverage of 90° x 90° (H x V). The MF/LF frequency range is covered by an 5" speaker. The integrated flying system includes 2 mounting points M10, which enables the installation of the U-bracket (included in delivery as standard). The flexible KIRA5 suits for speech and music applications as MF/HF speaker in sound reinforcement systems. The chassis is constructed from 15 mm plywood (birch) and covered with black texture finish. The cabinet is equipped with a front grill with transparent charcoal foam backing. Two speakon connectors (NL4) are mounted at the rear side of the chassis for signal input (input) and signal link (link). The power rating of the KIRA5 is 150 W (RMS), the impedance is 16 ohms.



KIRA5

5"/2-WAY COAXIAL PREMIUM LOUDSPEAKER/150 W (RMS)

PRODUCT DETAILS

KEY FEATURES

HF compression driver with 1.35" voice coil

High resolution coaxial 2-way transducer

90° x 90° nominal coverage

Passive fullrange operation

U-bracket included in delivery (as standard)

Ultra compact design and light weight

Monitor angle (45°)

SPECIFICATIONS

System Type	5", two-way, coaxial, monitor angle 45°
Frequency Range (-10 dB)	85 Hz - 20 kHz
Frequency Response (±3 dB)	95 Hz - 18 kHz
Coverage Pattern	90° x 90° nominal
HF Horn	Axisymmetric
Crossover Modes	Passive
Crossover Frequency	2.2 kHz
Power Rating (Continuous**/Program)	Passive
Maximum SPL ***	117 dB SPL peak
System Sensitivity (1w/1m)	92 dB SPL

KIRA5

5"/2-WAY COAXIAL PREMIUM LOUDSPEAKER/150 W (RMS)

LF Driver	1 x NOVA 5/150 COAX, 1.8" voice coil woofer
LF Nominal Impedance	16 ohms (passive)
MF Driver	n/a
MF Nominal Impedance	n/a
HF Driver	1 x NOVA 5/150 COAX, 1.35" voice coil driver
HF Nominal Impedance	16 ohms (passive)
Active Tunings	n/a (passive)
Enclosure	15 mm, plywood (multi layer)
Suspension / Mounting	2 x M10 mounting points
Transport	n/a
Finish	Black lacquer finish
Grille	Powder coated, black, perforated steel with acoustic transparent charcoal foam backing, NOVA logo
Input Connectors	2 x Neutrik® Speakon® NL4 1+/1- (2+/2- linked from input to output)
Dimensions (W x H x D)	160 mm x 160 mm x 180 mm
Net Weight	3 kg
Accessories	U-bracket, included in delivery as standard; LSA1: Adapter for speaker stand, (Art. no.