


XY-218S

# HIGH-POWER SUBWOOFER WITH TWO 18-INCH, LOW-FREQUENCY DRIVER.

---

A versatile PA/monitor speaker series that is compact in size and perfect for near-field monitoring – yet can deliver high-quality sound to the corners of the room. Boasts multiple installment options for easy set up.



XY-218S

# HIGH-POWER SUBWOOFER WITH TWO 18-INCH, LOW-FREQUENCY DRIVER.

## PRODUCT DETAILS

### KEY FEATURES

High-power subwoofer with two 18-inch, low-frequency drivers.

Capable of reproducing deep bass as low as 32 Hz without distortion.

Strong pillars installed in the cabinet ensure rigidity against the most powerful bass.

Requires an active crossover to set the necessary frequency range

NL4 INPUT and LINK OUT connections as standard.

Pole mount for quick set-up with other Pioneer products.

Robust enclosure made from premium multi-laminate birch plywood.

### SPECIFICATIONS

<b>Enclosure Type</b>	two drivers, reflex-loaded subwoofer
<b>Frequency Response</b>	32 Hz to 150 Hz
<b>Sensitivity (1 W/1 m)</b>	102 dB (half space)
<b>Nominal Impedance</b>	4 Ohm
<b>Power Handling</b>	1600 W RMS, 3200 W Program
<b>Maximum SPL</b>	134 dB cont., 140 dB peak (half space)
<b>Driver Configuration</b>	2 x 18 inch (460 mm) neodymium LF cone driver
<b>Connectors</b>	2 x Neutrik SpeakON™ NL4
<b>Dimensions (W×H×D)</b>	1164 x 558 x 745 mm (23.2 x 25.3 x 25.6 inch)
<b>Weight</b>	93 kg (205 lbs)

XY-218S

# HIGH-POWER SUBWOOFER WITH TWO 18-INCH, LOW-FREQUENCY DRIVER.

---

<b>Rigging and Hardware</b>	8 x flush handles (4 left/4 right), 4 x rubber feet (bottom) and 4 x mating recesses (top), 16 x threaded points M8 for 4 castors
<b>Grille</b>	Hex punched steel
<b>Enclosure</b>	18 mm (0.7 inch) birch plywood
<b>Finish</b>	Impact-resistant, Black semi-matt textured
<b>Suggested Power Amplifier</b>	K10DSP
<b>Accessories</b>	polemount socket cover(-W model only)