

SC42BK100PD

# SPEAKER CABLE XLR 3 PINS FEMALE - 1/4" JACK / 10 MT

These twinaxial speaker cable lines are a valid product to connect speaker systems with long cable run and large conductor areas or shorter bridge cables with lower power requirements. The section on 2.5 mm<sup>2</sup> satisfies a wide range of requirements. It is supplied with robust PE insulation and a flexible PVC jacket suitable to all sort of applications.



SC42BK100PD

# SPEAKER CABLE XLR 3 PINS FEMALE - 1/4" JACK / 10 MT

## PRODUCT DETAILS

### KEY FEATURES

Connectors: XLR 3 pins female SP36XLF / 1/4" Jack, 2 poles, gold plated tip SP14PPE INCO

Twinaxial BC86SPK speaker cable

Wire area: 2x 2.50 mm<sup>2</sup>

Cable diameter: 8.7 mm

PVC jacket

PE insulation grants very low capacity

Flexible, easy winding

Application: live, studio

Length: 10 mt

### SPECIFICATIONS

**Wire area** 2x 2.50 mm<sup>2</sup>

**Cable diameter** 8.7 mm

PVC jacket

**Connectors** XLR 3 pins female SP36XLF / 1/4" Jack, 2 poles, gold plated tip SP14PPE INCO