

# HMX-MIC

## PAGING MICROPHONE WITH CHIMES AND ZONE SELECTION FOR HMX-44/44A

The HMX-MIC is the ideal companion for all paging needs related to the use of the HELVIA HMX-44A matrix mixer. It is a gooseneck microphone with a microphone base powered by the HMX-44A central unit via RJ-45 cable. For lengths over 100m, the base can be connected to an external power supply (included).

The control panel allows selection of each of the 4 zones or all 4 simultaneously. The Chime function is programmable, and an additional stereo mini-jack AUX input is available. All levels (microphone, chime and AUX input) are adjustable.

HMX-MIC found or type unknown

ed9VJyF4mWfeS1707393490\_HMX-MIC Base 3Qtr.jpg

Q7T05ZNaNmXnNk1707393497\_HMX-MIC Rear.jpg



## HMX-MIC

# PAGING MICROPHONE WITH CHIMES AND ZONE SELECTION FOR HMX-44/44A

## PRODUCT DETAILS

### KEY FEATURES

Gooseneck microphone with level adjustment

Independent call control on each zone

ALL function for announcements on all zones

Programmable chime with level adjustment

Stereo mini-jack AUX input with level adjustment

RJ-45 connection with power supply

External power supply for distances over 100m

### SPECIFICATIONS

<b>Power Supply</b>	24Vdc, 500mA from RJ45 or power adaptor (included)
<b>Max. connection length</b>	100m (CAT5 cable) or 1km with 24Vdc adaptor (included)
<b>Capsule</b>	Back electret condenser
<b>Polar Pattern</b>	Cardioid
<b>Controls</b>	Aux/Mic/Chime levels, chime DIP switches, zone/page buttons
<b>Connectors</b>	RJ45 to amplifier, 24Vdc power jack, Aux input
<b>Frequency Response (-3dB)</b>	150Hz - 22kHz
<b>Input Level Mic</b>	-46dBV, Aux
<b>Input Impedance Mic</b>	600 Ohms, Aux
<b>Output Level</b>	10dBV

# HMX-MIC PAGING MICROPHONE WITH CHIMES AND ZONE SELECTION FOR HMX-44/44A

---

<b>Output Impedance</b>	balanced 600 Ohms
<b>S/N Ratio</b>	-60dB (all channels selected)
<b>Interface</b>	RS-485 control
<b>Zone assign</b>	4 zones or all selectable
<b>Product Size (WxDxH)</b>	115 x 143 x 460/53 (with Mic/without Mic) mm (4.52 x 5.63 x 18.11/2.09 in)
<b>Product Weight</b>	600 g. (1.32 lbs.)
<b>Packing Size (WxDxH)</b>	430 x 235 x 65 mm (16.93 x 9.25 x 2.56 in)
<b>Packing Weight</b>	1.06 kg (2.34 lbs.)