



XY-3B

DUAL 12" THREE-WAY HYBRID LOADED BI-AMP LOUDSPEAKER

In the XY-3B, an 8-inch cone driver delivers clean and precise mid-range frequencies using Pioneer Pro Audio's X-Phase system. A 1-inch compression driver produces crystal-clear HF which, thanks to the moulded Bi-horn, seamlessly blends with the mids. Two 12-inch drivers create tight, chest-pumping low mid.



XY-3B

DUAL 12" THREE-WAY HYBRID LOADED BI-AMP LOUDSPEAKER



XY-3B

DUAL 12" THREE-WAY HYBRID LOADED BI-AMP LOUDSPEAKER

PRODUCT DETAILS

KEY FEATURES

Moulded Bi-horn

X-Phase system with gold X-Phase plug

Hybrid low-mid section

Rigging and tour ready

SPECIFICATIONS

Frequency response 55 Hz?17 kHz

Sensitivity (1W/1m) LF?102 dB, MHF?107 dB

Nominal Impedance LF?4?, MHF?8?

Transformer taps LF?12-inch neodymium cone driver x 2, MF?8-inch neodymium cone driver, HF?1-inch exit neodymium compression driver

Power Handling LF?1200 W(RMS), 2400 W(Program), MHF?200 W(RMS), 400 W(Program)

Power Handling AES LF?133 dB(cont.), 139 dB(peak), MHF?130 dB(cont.), 136 dB(peak)

Dispersion speakON® NL4 x 2

3WAY Bi-amp loudspeaker

Enclosure 15 mm birch plywood

Dimensions (WxHxD) 530x1080x540 mm

Weight 57.6 kg