

LIVEMAKER 1521 MIX

1500W 2.1 PORTABLE PA SYSTEM WITH 8-CH MIXER, EFFECT, AND BLUETOOTH

The LIVEMAKER 1521 MIX, 1500W 2.1 PA system, is designed as a compact system for live and educational purposes. It integrates an 8-channel mixer with Digital Effects and Bluetooth, three Class-D amplifiers with switching power supply for 1500W total peak power, a generous 15" subwoofer and two satellites with a 8" woofer and 1.4" HF driver. It represents the perfect answer to those who need a professional sound system, but have problems of space, move with not very big cars or vans, and have a lot of audio sources to be connected. Not only, but they also need a professional reverb and, if necessary, want to connect a mobile phone, a tablet or a computer to play their play-lists. Both the subwoofer and the two tops are equipped with 36mm hole for pole or tripod. The reinforced MDF cabinets are robust, lightweight and finished with anti-scratch paint, to make them resistant to the rigors of the stage.



LIVEMAKER 1521 MIX

**1500W 2.1 PORTABLE PA SYSTEM WITH 8-CH MIXER,
EFFECT, AND BLUETOOTH**



LIVEMAKER 1521 MIX

1500W 2.1 PORTABLE PA SYSTEM WITH 8-CH MIXER, EFFECT, AND BLUETOOTH

PRODUCT DETAILS

KEY FEATURES

- 2.1 Compact PA System with 2 passive satellites and 1 active subwoofer
- 2 passive Tops with reinforced MDF cabinet, featuring 8" and 1.44" Titanium dome driver
- Active bass-reflex subwoofer with reinforced MDF enclosure, featuring a 15" woofer for up to 128dB sound pressure
- 8 Channel mixer with 4 MIC Inputs, 1 Stereo Line Input, 1 Stereo Bluetooth Input
- 2-Band EQ, 16 Digital Effects (Mic channels only)
- 1500W Peak power class-D amplifier with high-efficiency, low-heat dissipation switching power supply
- Balanced MIC/Line Inputs and Balanced Outputs
- Standard D36mm pole mount adapter over the subwoofer top and under the two satellites
- 2 handles on subwoofer (1 on each side)
- 1 Rear handle on each top

SPECIFICATIONS

System Max SPL	129 dB
System Frequency Response	40 Hz-20 kHz
Satellite Power RMS / Peak	300W / 600W (each)
Satellite Frequency Response	80 Hz-20 kHz
Satellite Sensitivity (1W@1m)	97 dB
Satellite Max. SPL (@1m)	122 dB
Satellite nominal Impedance	8 ohms

LIVEMAKER 1521 MIX

1500W 2.1 PORTABLE PA SYSTEM WITH 8-CH MIXER, EFFECT, AND BLUETOOTH

Satellites Input Connectors		2 x Speakon
Satellite LF	1 x 8" with 2" voice coil	
Satellite HF	1 x 1.4" voice coil, titanium dome	
Satellite Crossover Frequency	3 kHz, 12 dB/octave	
Speaker Pole Adapter	Ø36mm	
Satellite Size (WxHxD)	614x510x334 mm (2pcs carton); 270x450x245 mm (one speaker)	
Satellite Weight	Net weight 9.2kg; Gross weight 20kgs (2pcs carton)	
Inputs	MIC XLR, 6.3mm jack, RCA	
EQ Control	Low	
Bluetooth connection distance	>6m	
Subwoofer amplifier	1 x 500W RMS @ 4ohms	
Satellites amplifier	2x 250W RMS @ 8ohms	
Sub LF driver	15" with 3" voice coil.	
Sub Frequency response	40 Hz-150 Hz	
Sub Sensitivity (1m/1W)	98 dB	
Sub Max. SPL (@1m)	128 dB	
Mains	AC 230V 50Hz (Fuse	
Subwoofer Size (WxHxD)	810x725x580 mm (Packing); 465x620x650 mm (sub)	
Subwoofer Net Weight	net weight 31.4kg; packing 35kg	
Housing material	MDF + Anti-scratch Printing (Black finish)	
Handles	2 on subwoofer (1 on each side); 1 on rear side of each top	
Pole Mount Adapter	Standard ;20	