

MTP550SW

DYNAMIC MICROPHONE FOR PRO LEVEL STAGE

The LEWITT MTP 550 DM and MTP 550 DMs both focus on the main qualities of a professional handheld performance microphone – high gain before feedback, detailed, rich and authentic sound, easy handling and ruggedness. The MTP 550 DM and DMs feature a new improved internal shock-mount - the capsule of the MTP 550 DM and DMs is fully rubber-mounted enabling exceptionally low handling noise. A built-in spherical wind and pop filter compliments specially tailored frequency response to ensure consistently rich and powerful output in any setting. The new and smaller switch on the MTP 550 DMs efficiently prevents accidental operation and reduces unwanted handling noise. These high-performance cardioid dynamic handheld microphones should be part in any professional set of live microphones.

MTP550SW and or type unknown

MTP550SW

DYNAMIC MICROPHONE FOR PRO LEVEL STAGE

PRODUCT DETAILS

KEY FEATURES

Frequency response shaped specifically for demanding vocal applications, with brightened midrange and bass roll-off

Uniform cardioid pickup pattern for maximum isolation of the main sound source

Easily withstands high sound pressure levels

Effective integrated acoustic pop and windshield offers excellent protection without compromising high-frequency clarity

Rock-solid full-metal, die-cast body for rough daily touring routine

Hardened hexagonal ruthenium-galvanized steel mesh grille to prevent wear and abuse

Minimally affected by varying load impedance

The MTP 550 DMs features a convenient recessed on/off slide switch

Corrosion-resistant gold-plated 3-pin XLR output connector

Comes in a cardboard box with foam layers; includes MTP 40 MCs shock mount and DTP 40 Lb artificial leather bag

Top applications: Lead and background vocals, Live-Interviews

SPECIFICATIONS

Acoustical operating principle dynamic, moving coil

Directional pattern cardioid

Frequency range 60 ... 16.000 Hz

Sensitivity 2 mV / Pa (-54 dBV)

Rated impedance < 300 ohms

Connector gold plated 3-pin XLR

Dimensions 49 dia. x 175 mm / 1,9 dia. x 6,9 inch

Net weight:400g / 14,1 oz