

CM-S56T-K 6" SURFACE MOUNT LOUDSPEAKER (COUPLE)

Drawing on our club loudspeaker manufacturing heritage, the versatile two-way CM-S54T, CM-S56T and CM-S58T produce premium-quality audio. Available in black or white, these new units are perfect for discreet installation in a variety of spaces where reliability is crucial, and the loudspeakers can even be used for some applications outdoors.

These affordable and adaptable new arrivals in the CM Series include a host of features including transformer taps – ideal if you need a professional and adaptable fixed installation solution.

CM-S56T-K and or type unknown

hZzgtMMjkeBTQr1651739041_CM-S56T-K_angle_no-grill_9818.png

s13ZEnv9sc2Vbbm1651739041_CM-S56T-K.png

CM-S56T-K

6" SURFACE MOUNT LOUDSPEAKER (COUPLE)

PRODUCT DETAILS

KEY FEATURES

Soft dome tweeter

Newly developed Vortex Bass Accelerator

Flexible 8 ohms impedance

Dust and water resistant

U bracket

Original curved enclosure design

Color: Black

SPECIFICATIONS

Two-way passive, reflex-loaded

Frequency response (- 10 dB, Typical) 80 Hz - 20 kHz

Sensitivity (1W/1m) 88 dB

Nominal Impedance 8 ?

Power Handling (RMS/Program) 60 W / 120 W * IEC60268-5

Transformer taps 70 V 60 W / 30 W / 15 W / 7.5 W

Transformer taps 100 V 60 W / 30 W / 15 W

Dispersion 110 °H x 110 °V

Maximum SPL 113 dB (peak) * Calculated from the power handling and sensitivity

LF 6" (152 mm) cone

HF 1" (25 mm) silk dome tweeter

Connectors Euroblock (4 pin) x 1 (input +/-, loop-thru

CM-S56T-K

6" SURFACE MOUNT LOUDSPEAKER (COUPLE)

Rigging and Hardware	1 x U-bracket 2 x M6 threaded mounting points on rear
-----------------------------	---

Grille	Punched Aluminum
---------------	------------------

Enclosure PP

Dimensions (WxHxD) 214.1 x 332.3 x 183.5 mm
--

Weight	5.1 kgs
---------------	---------

Environmental IP54
