

MOODLINER 1430WP 14X30W RGBW 4IN1 WATERPROOF LED BAR WASHER

Centolight MOODLINER 1420WP is an Outdoor Wash Led Bar with a 25° beam angle. The light source consists of 14pcs of 30W 4in1 Led with RGBW color mixing. The DMX control (with RDM) allows you to control every single color of each LED independently, allowing extremely rich polychromatic effects. The MOODLINER 1430WP is designed for outdoor architectural applications or in all those situations where color wash effect as well as totally silent operation are required (theaters, houses of worship, museums, auditoriums, etc.).

The fixture structure is very stout and completely waterproof. The housing is made of die-cast aluminum and steel parts, with high-quality rubber gaskets for maximum isolation and resistance to time. PowerCon In/Out Power connections and DMX In/Out connections with XLR are totally waterproof.

MOODLINER 1430WP unknown

twyPEgTnGN71zs1664966044_Moodliner 1430WP 3Qtr 2.jpg

zsigBYmqDuU07Fi1664966054_Moodliner 1430W

SGbEkz61qkYWK41664966088_Moodliner 1430WP Connector.jpg

5TF1pyy6gZWeWD31664966092_Moodliner

MOODLINER 1430WP

14X30W RGBW 4IN1 WATERPROOF LED BAR WASHER

PRODUCT DETAILS

KEY FEATURES

Waterproof Washer Bar with 25° Beam Angle

14x30W RGBW 4in1 LED with over 50,000h lifetime

Luminous Flux: (RGBW) 3082lux/3m, 794lux/7m

CRI: Ra?85

Flicker Free Operation

Smooth 16-bit Dimmer

Silent Operation

IP65 Protection Degree

Waterproof DMX and Power connections

SPECIFICATIONS

Light Source 14x30W RGBW 4in1 LED

Chip Life over 50,000h

Luminous Flux (R) 573lux/3m, 152lux/7m; (G) 878lux/3m, 209lux/7m; (B) 886lux/3m, 217lux/7m; (W) 1078lux/3m, 295lux/7m; (RGBW) 3082lux/3m, 794lux/7m;

CRI Ra?85

Refresh Rate over 4.000Hz (Flicker-Free)

Beam Angle 25°

Dimmer 16-Bit Smooth Linear Dimming

MOODLINER 1430WP

14X30W RGBW 4IN1 WATERPROOF LED BAR WASHER

Strobe effect

Cooling System	Convection (without fan)
DMX Channel Modes	9/23/56/65 Channels (RDM Included)
Control Modes	DMX, Master-Slave, Sound, Auto Run, Manual Dimming
Control Panel	4 Buttons and LED Display
IP rate	IP65
Housing	Aluminum + Steel
DMX In/Out	Waterproof 3-pin XLR
Power Socket	Waterproof Powercon In/Out
Voltage:100~240V 50/60Hz	
Max Power Consumption	450W
Working Temperature	-30÷55°C
Fixture Size (WxDxH)	1012x139x138,5 mm max. – 39.84x5.47x5.45 in (feet included)
Net Weight	7,2 kg – 15.87 lbs.
Packing Size (WxDxH)	1040x170x220mm – 40.94x6.69x8.66 in
Packing Weight	8,3 kg – 18.3 lbs.